

AUTOMATED BUTTERFLY VALVES Schneider Electric SmartX ACTUATORS





ACTUATOR PART # * = DUAL ACTUATORS	SIZE	A DIM.	B DIM.	C DIM.	Cv	Max. Close Rating	Bubble Leak Occur.
Mx41-615x,Mx4x-715x,717x	2	4.5	7 1/2	1 5/8	84	125	125#
Mx41-615x,Mx4x-715x,717x	2.5	5.0	8 1/4	1 3/4	163	125	125#
Mx41-615x,Mx4x-715x,717x	3	5.5	9 3/16	1 3/4	267	110	125#
Mx41-615x,Mx4x-715x,717x	4	6.5	10 3/4	2.0	496	110	50#
Mx41-615x,Nx4x-715x,717x	5	7.5	12 1/4	2 1/8	775	95	50#
Mx41-615x,Mx4x-715x,717x	6	8.0	13 15/16	2 1/8	1025	85	50#
Mx41-634x,Mx41-730x	8	9.0	14 7/8	2 1/2	1862	85	50#
Mx41-634x,Mx41-730x	10	11	17 3/4	2 1/2	2948	75	50#
Mx41-634x,*Mx41-730x	12	12	19 3/4	3.0	4393	60	50#
*Mx41-634x,*Mx41-730x	14	14	21 3/4	3.0	5939	70	50#
*Mx41-634x,*Mx41-730x	16	15	24 3/4	4.0	7867	60	50#

System pressure is normally not a resistance factor For 3-way valve disc closure




Schneider Electric ACTUATORS





For Best Modulating Control Results Valves Are Adjusted For 70 Deg Max Opening

Ratings are Based on Bray S31 & Pratt BF-8688-1 Valve Bodies



2: A CLOSED B OPEN
3: A OPEN B CLOSED
4: A CLOSED C OPEN
5: A OPEN C CLOSED
6: C CLOSED B OPEN
7: C OPEN B CLOSED

3-WAY VALVE ORIENTATIONS


STANDARD VALVE BODY FEATURES

- ☐ **EPDM Rubber liner**
- ☐ **Stainless Steel or Nylon Coated Disc**
- ☐ **Stainless Steel Shaft**
- ☐ **Full Threaded Lug**


SIZE	CV VALUES							
2	144	84	61	43	27	16	7	1
2.5	282	163	107	67	43	24	11	1.5
3	461	267	154	96	61	35	15	2
4	841	496	274	171	109	62	27	3
5	1,376	775	428	268	170	98	43	5
6	1,850	1,025	567	354	225	129	56	6
8	3,316	1,862	1,081	680	421	241	102	12
10	5,430	2,948	1,710	1,076	667	382	162	19
12	8,077	4,393	2,563	1,594	1,005	555	235	27
14	10,538	5,939	3,384	2,149	1,320	756	299	34
16	13,966	7,867	4,483	2,847	1,749	1,001	397	45
	90°	70°	60	50°	40°	30°	20°	10°


BVE -SCH -2W -Y -ZZ -06 -BS-B

- BUTTERFLY VALVE-ELECTRIC
- SCHNEIDER SMART X ACTUATOR
- 2-WAY OR 3-WAY
- A 0-10 VDC/4-20mA
- B OPEN CLOSE OR FLOATING
- NC, NO, or 3-WAY ORIENTATION #
- VALVE SIZE EX. 6"=06



Full Lug Body is Standard





DIMENSIONS

SIZE	A	B	D	E	F	G	H	J	K
2"	3.69	1.62	2.84	5.50	3.54	.55	.39	1.25	1.32
2.5"	4.19	1.75	3.34	6.00	3.54	.55	.39	1.25	1.91
3"	4.88	1.75	4.03	6.25	3.54	.55	.39	1.25	2.55
4"	6.06	2.00	5.16	7.00	3.54	.63	.43	1.25	3.57
5"	7.12	2.12	6.16	7.50	3.54	.75	.51	1.25	4.63
6"	8.12	2.12	7.02	8.00	3.54	.75	.51	1.25	5.45
8"	10.50	2.50	9.47	9.50	5.91	.87	.63	1.25	7.45
10"	12.75	2.50	11.47	10.75	5.91	1.18	.87	2.00	9.53
12"	14.88	3.00	9.47	9.50	5.91	1.18	.87	2.00	11.47
14"	17.05	3.00	15.28	13.62	5.91	1.38	N/A	2.00	13.04
16"	19.21	4.00	17.41	14.75	5.91	1.38	N/A	2.00	14.85

Part Numbering System

BS = Valve Bump Switch
VPI = Visual Pos Indicator
Aux = Actuator Aux Sw
SR = Spring Return
B = Bray P = Pratt
WP = NEMA 4 WeatherProof

WESLEY VALVE CO.
MFGRS OF AUTOMATED BUTTERFLY VALVES
PHN: (404) 351-8744
FAX: (404) 351-9340
www.wesleyvalve.com

File:TACSXData